


Solid Pure Ceiling/Wall No Dimmable

■ 09.2865.14 - Black

Spotlight to be installed on ceiling/wall with LED light source. 220-240V, 50-60Hz power supply included.

Spotlight to be installed on ceiling/wall with LED light source. 220-240V, 50-60Hz power supply included.




Main specifications

| | | | |
|------------------------|-------|-----------------------|---------------------|
| Number of heads | 1 | Net lumen (lm) | 2355 |
| Lamp category | LED | Mountings | Surface |
| Power (W) | 23W | Environment | Indoor dry location |
| CCT (K) | 4000K | | |
| CRI | 80 | | |

Optical

| | |
|-------------------------------|-----------|
| Lighting type | Direct |
| LED type | LED array |
| Light distribution | Symmetric |
| Optical type | Spot |
| Beam angle (°) | 10 |
| Beam angle C90-270 (°) | 10 |



| | | | |
|--------------------|-------------|--------------|-------------|
| Beam Angle: | 10° | | |
| | h(m) | E(lx) | D(m) |
| 1 | 29499 | 0.18 | |
| 2 | 7375 | 0.35 | |
| 3 | 3278 | 0.53 | |
| 4 | 1844 | 0.71 | |
| 5 | 1180 | 0.88 | |


Luminous flux luminaire
2355 lm

Electrical

| | | | |
|-----------------------|--------------|-------------------------|---|
| Frequency (Hz) | 50/60 | Insulation class | I |
| Dimmable | No | | |
| Driver | Integrated | | |
| Driver type | Non Dimmable | | |
| Emergency | Without | | |

Physical


| | |
|---------------------|------------|
| Color | Black |
| Orientation | Adjustable |
| Weight (kg) | 1.90 |
| Rotation (°) | 360 |



Solid Pure Ceiling/Wall No Dimmable




Honeycomb anti-glare screen
08.8763.14




Amber filter
08.8766.66.OD




Holding ring
08.8768.14



Sky blue filter
08.8766.65.OD



Red filter
08.8766.67.OD



Blue filter
08.8766.64.OD