



## Solid Pure Ceiling/Wall No Dimmable

### ■ 09.2866.14 - Black

Spotlight to be installed on ceiling/wall with LED light source. 220-240V, 50-60Hz power supply included.


Spotlight to be installed on ceiling/wall with LED light source. 220-240V, 50-60Hz power supply included.

### Main specifications

|                 |       |                |                     |
|-----------------|-------|----------------|---------------------|
| Number of heads | 1     | Net lumen (lm) | 2044                |
| Lamp category   | LED   | Mountings      | Surface             |
| Power (W)       | 23W   | Environment    | Indoor dry location |
| CCT (K)         | 4000K |                |                     |
| CRI             | 80    |                |                     |

### Optical


|                        |           |
|------------------------|-----------|
| Lighting type          | Direct    |
| LED type               | LED array |
| Light distribution     | Symmetric |
| Optical type           | Medium    |
| Beam angle (°)         | 18        |
| Beam angle C90-270 (°) | 18        |



Beam Angle: 18°

|   | h(m)  | E(lx) | D(m) |
|---|-------|-------|------|
| 1 | 12318 | 0.31  |      |
| 2 | 3080  | 0.62  |      |
| 3 | 1369  | 0.93  |      |
| 4 | 770   | 1.24  |      |
| 5 | 493   | 1.55  |      |

Luminous flux luminaire  
2044 lm




### Electrical



|                |              |                  |   |
|----------------|--------------|------------------|---|
| Frequency (Hz) | 50/60        | Insulation class | I |
| Dimmable       | No           |                  |   |
| Driver         | Integrated   |                  |   |
| Driver type    | Non Dimmable |                  |   |
| Emergency      | Without      |                  |   |

### Physical

|              |            |
|--------------|------------|
| Color        | Black      |
| Orientation  | Adjustable |
| Weight (kg)  | 1.90       |
| Rotation (°) | 360        |



Solid Pure Ceiling/Wall No Dimmable



---


Sky blue filter  
08.8766.65.OD

---

Blue filter  
08.8766.64.OD

---

Honeycomb anti-glare screen  
08.8763.14



---

Holding ring  
08.8768.14

---

Red filter  
08.8766.67.OD

---

Amber filter  
08.8766.66.OD