


## Solid Pure Ceiling/Wall No Dimmable

■ 09.2867.30 - White

Spotlight to be installed on ceiling/wall with LED light source. 220-240V, 50-60Hz power supply included.

Spotlight to be installed on ceiling/wall with LED light source. 220-240V, 50-60Hz power supply included.




## Main specifications

|                 |       |                |                     |
|-----------------|-------|----------------|---------------------|
| Number of heads | 1     | Net lumen (lm) | 2213                |
| Lamp category   | LED   | Mountings      | Surface             |
| Power (W)       | 23W   | Environment    | Indoor dry location |
| CCT (K)         | 4000K |                |                     |
| CRI             | 80    |                |                     |

## Optical

|                        |           |
|------------------------|-----------|
| Lighting type          | Direct    |
| LED type               | LED array |
| Light distribution     | Symmetric |
| Optical type           | Flood     |
| Beam angle (°)         | 35        |
| Beam angle C90-270 (°) | 35        |



Beam Angle: 35°

|   | h(m) | E(lx) | D(m) |
|---|------|-------|------|
| 1 | 5662 | 0.64  |      |
| 2 | 1415 | 1.27  |      |
| 3 | 629  | 1.91  |      |
| 4 | 354  | 2.54  |      |
| 5 | 226  | 3.18  |      |

Luminous flux luminaire  
2213 lm

## Electrical


|                |              |                  |   |
|----------------|--------------|------------------|---|
| Frequency (Hz) | 50/60        | Insulation class | I |
| Dimmable       | No           |                  |   |
| Driver         | Integrated   |                  |   |
| Driver type    | Non Dimmable |                  |   |
| Emergency      | Without      |                  |   |

## Physical

|              |            |
|--------------|------------|
| Color        | White      |
| Orientation  | Adjustable |
| Weight (kg)  | 1.90       |
| Rotation (°) | 360        |



Solid Pure Ceiling/Wall No Dimmable



---



Blue filter  
08.8766.64.OD

---

Honeycomb anti-glare screen  
08.8763.14

---

Holding ring  
08.8768.14



---

Red filter  
08.8766.67.OD

---

Amber filter  
08.8766.66.OD

---

Sky blue filter  
08.8766.65.OD