Solid Pure Ceiling/Wall No Dimmable

09.2873.14 - Black

Spotlight to be installed on ceiling/wall with LED light source. 220-240V, 50-60Hz power supply included.

Spotlight to be installed on ceiling/wall with LED light source. 220-240V, 50-60Hz power supply included.



Main specifications

Number of heads	1	**Net lumen (lm)**	2516
Lamp category	LED	**Mountings**	Surface
Power (W)	30W	**Environment**	Indoor dry location
CCT (K)	3000K		
CRI	90		

Optical

Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Spot
Beam angle (°)	14
Beam angle C90-270 (°)	14



Luminous flux luminaire
2516 lm

Beam Angle: 14°

h(m)	E(lx)	D(m)
1	17856	0.25
2	4464	0.51
3	1984	0.76
4	1116	1.01
5	714	1.27

Electrical

Frequency (Hz)	50/60	**Insulation class**	I
Dimmable	No		
Driver	Integrated		
Driver type	Non Dimmable		
Emergency	Without		

Physical

Color	Black
Orientation	Adjustable
Weight (kg)	1.90
Rotation (°)	360

Solid Pure Ceiling/Wall No Dimmable

Holding ring
08.8768.14



Amber filter
08.8766.66.OD



Sky blue filter
08.8766.65.OD



Blue filter
08.8766.64.OD

Honeycomb anti-glare screen
08.8763.14



Red filter
08.8766.67.OD