


## Solid Pure Ceiling/Wall No Dimmable

09.2962.30 - White

Spotlight to be installed on ceiling/wall with LED light source. 220-240V, 50-60Hz power supply included.

Spotlight to be installed on ceiling/wall with LED light source. 220-240V, 50-60Hz power supply included.




### Main specifications

<b>Number of heads</b>	1	<b>Net lumen (lm)</b>	3695
<b>Lamp category</b>	LED	<b>Mountings</b>	Surface
<b>Power (W)</b>	35W	<b>Environment</b>	Indoor dry location
<b>CCT (K)</b>	4000K		
<b>CRI</b>	80		

### Optical

<b>Lighting type</b>	Direct
<b>LED type</b>	LED array
<b>Light distribution</b>	Symmetric
<b>Optical type</b>	Spot
<b>Beam angle (°)</b>	15
<b>Beam angle C90-270 (°)</b>	15



Beam Angle: 15°

h(m) E(lx) D(m)

1 25076 0.26

2 6269 0.53

3 2786 0.79

4 1567 1.05

5 1003 1.31


Luminous flux luminaire  
3695 lm

### Electrical



<b>Frequency (Hz)</b>	50/60	<b>Insulation class</b>	I
<b>Dimmable</b>	No		
<b>Driver</b>	Integrated		
<b>Driver type</b>	Non Dimmable		
<b>Emergency</b>	Without		

### Physical

<b>Color</b>	White
<b>Orientation</b>	Adjustable
<b>Weight (kg)</b>	1.90
<b>Rotation (°)</b>	360



## Solid Pure Ceiling/Wall No Dimmable



---



Sky blue filter  
08.8766.65.OD

---

Holding ring  
08.8768.14

---

Blue filter  
08.8766.64.OD



---

Red filter  
08.8766.67.OD

---

Amber filter  
08.8766.66.OD

---

Honeycomb anti-glare screen  
08.8763.14