


Solid Pure Ceiling/Wall No Dimmable

09.2964.30 - White

Spotlight to be installed on ceiling/wall with LED light source. 220-240V, 50-60Hz power supply included.

Spotlight to be installed on ceiling/wall with LED light source. 220-240V, 50-60Hz power supply included.




Main specifications

| | | | |
|------------------------|-------|-----------------------|---------------------|
| Number of heads | 1 | Net lumen (lm) | 3695 |
| Lamp category | LED | Mountings | Surface |
| Power (W) | 35W | Environment | Indoor dry location |
| CCT (K) | 4000K | | |
| CRI | 80 | | |

Optical

| | |
|-------------------------------|-----------|
| Lighting type | Direct |
| LED type | LED array |
| Light distribution | Symmetric |
| Optical type | Flood |
| Beam angle (°) | 45 |
| Beam angle C90-270 (°) | 45 |



| | | | |
|--------------------|-------------|--------------|-------------|
| Beam Angle: | 45° | | |
| | h(m) | E(lx) | D(m) |
| 1 | 7522 | 0.83 | |
| 2 | 1880 | 1.65 | |
| 3 | 836 | 2.48 | |
| 4 | 470 | 3.31 | |
| 5 | 301 | 4.13 | |


Luminous flux luminaire
3695 lm

Electrical


| | | | |
|-----------------------|--------------|-------------------------|---|
| Frequency (Hz) | 50/60 | Insulation class | I |
| Dimmable | No | | |
| Driver | Integrated | | |
| Driver type | Non Dimmable | | |
| Emergency | Without | | |

Physical


| | |
|---------------------|------------|
| Color | White |
| Orientation | Adjustable |
| Weight (kg) | 1.90 |
| Rotation (°) | 360 |




Solid Pure Ceiling/Wall No Dimmable



Blue filter
08.8766.64.OD




Amber filter
08.8766.66.OD



Sky blue filter
08.8766.65.OD



Holding ring
08.8768.14



Red filter
08.8766.67.OD



Honeycomb anti-glare screen
08.8763.14