Solid Pure Ceiling/Wall No Dimmable

09.2970.30 - White

Spotlight to be installed on ceiling/wall with LED light source. 220-240V, 50-60Hz power supply included.

Spotlight to be installed on ceiling/wall with LED light source. 220-240V, 50-60Hz power supply included.



Main specifications

Number of heads	1	**Net lumen (lm)**	4609
Lamp category	LED	**Mountings**	Surface
Power (W)	53W	**Environment**	Indoor dry location
CCT (K)	3000K		
CRI	80		

Optical

Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Flood
Beam angle (°)	45
Beam angle C90-270 (°)	45



Luminous flux luminaire
4609 lm

Beam Angle: 45°

h(m)	E(lx)	D(m)
1	9417	0.82
2	2354	1.65
3	1046	2.47
4	589	3.30
5	377	4.12

Electrical

Frequency (Hz)	50/60	**Insulation class**	I
Dimmable	No		
Driver	Integrated		
Driver type	Non Dimmable		
Emergency	Without		

Physical

Color	White
Orientation	Adjustable
Weight (kg)	1.90
Rotation (°)	360

Solid Pure Ceiling/Wall No Dimmable



Amber filter
08.8766.66.OD

Holding ring
08.8768.14



Red filter
08.8766.67.OD



Blue filter
08.8766.64.OD

Honeycomb anti-glare screen
08.8763.14



Sky blue filter
08.8766.65.OD