



Solid Pure Ceiling/Wall No Dimmable

■ 09.2980.14 - Black

Spotlight to be installed on ceiling/wall with LED light source. 220-240V, 50-60Hz power supply included.


Spotlight to be installed on ceiling/wall with LED light source. 220-240V, 50-60Hz power supply included.

Main specifications

Number of heads	1	Net lumen (lm)	3848
Lamp category	LED	Mountings	Surface
Power (W)	53W	Environment	Indoor dry location
CCT (K)	3000K		
CRI	90		

Optical

Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Spot
Beam angle (°)	15
Beam angle C90-270 (°)	15



Beam Angle: 15°

h(m) E(lx) D(m)

1 26199 0.26

2 6550 0.52

3 2911 0.78

4 1637 1.05

5 1048 1.31



Luminous flux luminaire
3848 lm

Electrical

Frequency (Hz)	50/60	Insulation class	I
Dimmable	No		
Driver	Integrated		
Driver type	Non Dimmable		
Emergency	Without		

Physical


Color	Black
Orientation	Adjustable
Weight (kg)	1.90
Rotation (°)	360



Solid Pure Ceiling/Wall No Dimmable




Holding ring
08.8768.14




Blue filter
08.8766.64.OD




Honeycomb anti-glare screen
08.8763.14



Amber filter
08.8766.66.OD



Sky blue filter
08.8766.65.OD



Red filter
08.8766.67.OD