

## Solid Pure Track Dali Version

09.2872.30.DA - White


Spotlight to be installed on 3-phase track with LED light source. 220-240V, 50-60Hz power supply included.

### Main specifications

Number of heads	1	Net lumen (lm)	2662
Lamp category	LED	Mountings	Track
Power (W)	30W	Environment	Indoor dry location
CCT (K)	3000K		
CRI	80		

### Optical

Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Flood
Beam angle (°)	44
Beam angle C90-270 (°)	44



Beam Angle:	44°		
	h(m)	E(lx)	D(m)
1	5623	0.80	
2	1406	1.61	
3	625	2.41	
4	351	3.22	
5	225	4.02	

Luminous flux luminaire  
2662 lm

### Electrical

Frequency (Hz)	50/60	Insulation class	I
Dimmable	Yes		
Driver	Integrated		
Driver type	Dimmable DALI		
	1		
Emergency	Without		

### Physical

Color	White
Orientation	Adjustable
Weight (kg)	1.70
Rotation (°)	360

## Solid Pure Track Dali Version




---

Honeycomb anti-glare screen  
08.8763.14




---

Holding ring  
08.8768.14




---

Sky blue filter  
08.8766.65.OD




---

Blue filter  
08.8766.64.OD



---

Red filter  
08.8766.67.OD



---

Amber filter  
08.8766.66.OD