

## Solid Pure Track Dali Version

09.2880.30.DA - White


Spotlight to be installed on 3-phase track with LED light source. 220-240V, 50-60Hz power supply included.

### Main specifications

<b>Lamp category</b>	LED	<b>Mountings</b>	Track
<b>Power (W)</b>	30W	<b>Environment</b>	Indoor
<b>CCT (K)</b>	4000K		
<b>CRI</b>	80		
<b>Net lumen (lm)</b>	3200		

### Optical

<b>Lighting type</b>	Direct
<b>LED type</b>	LED array
<b>Light distribution</b>	Symmetric
<b>Optical type</b>	Medium
<b>Beam angle (°)</b>	22
<b>Beam angle C90-270 (°)</b>	22



Beam Angle: 22°

	h(m)	E(lx)	D(m)
1	13910	0.39	
2	3478	0.79	
3	1546	1.18	
4	869	1.57	
5	556	1.97	

Luminous flux luminaire  
3200 lm


### Electrical

<b>Frequency (Hz)</b>	50/60
<b>Dimmable</b>	Yes
<b>Driver</b>	Integrated
<b>Emergency</b>	Without
<b>Insulation class</b>	I

### Physical

<b>Color</b>	White
<b>Orientation</b>	Adjustable
<b>Weight (kg)</b>	1.70
<b>Rotation (°)</b>	360

### Certification / Marking




## Solid Pure Track Dali Version




---

Honeycomb anti-glare screen  
08.8763.14




---

Blue filter  
08.8766.64.OD




---

Sky blue filter  
08.8766.65.OD



---

Amber filter  
08.8766.66.OD



---

Red filter  
08.8766.67.OD



---

Holding ring  
08.8768.14