

## Solid Pure Track Dali Version

■ 09.2886.14.DA - Black


Spotlight to be installed on 3-phase track with LED light source. 220-240V, 50-60Hz power supply included.

### Main specifications

|                        |       |                       |                     |
|------------------------|-------|-----------------------|---------------------|
| <b>Number of heads</b> | 1     | <b>Net lumen (lm)</b> | 1637                |
| <b>Lamp category</b>   | LED   | <b>Mountings</b>      | Track               |
| <b>Power (W)</b>       | 23W   | <b>Environment</b>    | Indoor dry location |
| <b>CCT (K)</b>         | 3000K |                       |                     |
| <b>CRI</b>             | 90    |                       |                     |

### Optical

|                               |           |
|-------------------------------|-----------|
| <b>Lighting type</b>          | Direct    |
| <b>LED type</b>               | LED array |
| <b>Light distribution</b>     | Symmetric |
| <b>Optical type</b>           | Medium    |
| <b>Beam angle (°)</b>         | 18        |
| <b>Beam angle C90-270 (°)</b> | 18        |



|                        |              |             |
|------------------------|--------------|-------------|
| <b>Beam Angle: 18°</b> |              |             |
| <b>h(m)</b>            | <b>E(lx)</b> | <b>D(m)</b> |
| 1                      | 9864         | 0.31        |
| 2                      | 2466         | 0.62        |
| 3                      | 1096         | 0.93        |
| 4                      | 616          | 1.24        |
| 5                      | 395          | 1.55        |

Luminous flux luminaire  
1637 lm


### Electrical

|                       |               |                         |   |
|-----------------------|---------------|-------------------------|---|
| <b>Frequency (Hz)</b> | 50/60         | <b>Insulation class</b> | I |
| <b>Dimmable</b>       | Yes           |                         |   |
| <b>Driver</b>         | Integrated    |                         |   |
| <b>Driver type</b>    | Dimmable DALI |                         |   |
|                       | 1             |                         |   |
| <b>Emergency</b>      | Without       |                         |   |

### Physical


|                     |            |
|---------------------|------------|
| <b>Color</b>        | Black      |
| <b>Orientation</b>  | Adjustable |
| <b>Weight (kg)</b>  | 1.70       |
| <b>Rotation (°)</b> | 360        |

## Solid Pure Track Dali Version




---

Sky blue filter  
08.8766.65.OD



---

Amber filter  
08.8766.66.OD



---

Red filter  
08.8766.67.OD




---

Holding ring  
08.8768.14



---

Honeycomb anti-glare screen  
08.8763.14



---

Blue filter  
08.8766.64.OD