

## Solid Pure Track Dali Version

09.2960.30.DA - White


Spotlight to be installed on 3-phase track with LED light source. 220-240V, 50-60Hz power supply included.

### Main specifications

|                 |       |                |                     |
|-----------------|-------|----------------|---------------------|
| Number of heads | 1     | Net lumen (lm) | 3614                |
| Lamp category   | LED   | Mountings      | Track               |
| Power (W)       | 35W   | Environment    | Indoor dry location |
| CCT (K)         | 4000K |                |                     |
| CRI             | 80    |                |                     |

### Optical

|                        |           |
|------------------------|-----------|
| Lighting type          | Direct    |
| LED type               | LED array |
| Light distribution     | Symmetric |
| Optical type           | Medium    |
| Beam angle (°)         | 23        |
| Beam angle C90-270 (°) | 23        |



Beam Angle: 23°

| h(m) | E(lx) | D(m) |
|------|-------|------|
| 1    | 15402 | 0.40 |
| 2    | 3850  | 0.80 |
| 3    | 1711  | 1.20 |
| 4    | 963   | 1.59 |
| 5    | 616   | 1.99 |

Luminous flux luminaire  
3614 lm


### Electrical

|                |               |                  |   |
|----------------|---------------|------------------|---|
| Frequency (Hz) | 50/60         | Insulation class | I |
| Dimmable       | Yes           |                  |   |
| Driver         | Integrated    |                  |   |
| Driver type    | Dimmable DALI |                  |   |
|                | 1             |                  |   |
| Emergency      | Without       |                  |   |

### Physical

|              |            |
|--------------|------------|
| Color        | White      |
| Orientation  | Adjustable |
| Weight (kg)  | 1.70       |
| Rotation (°) | 360        |

Solid Pure Track Dali Version




---

Red filter  
08.8766.67.OD




---

Amber filter  
08.8766.66.OD



---

Sky blue filter  
08.8766.65.OD



---

Blue filter  
08.8766.64.OD



---

Honeycomb anti-glare screen  
08.8763.14



---

Holding ring  
08.8768.14