



## Solid Pure Track Dali Version

■ 09.2961.14.DA - Black

Spotlight to be installed on 3-phase track with LED light source. 220-240V, 50-60Hz power supply included.


### Main specifications

Number of heads	1	Net lumen (lm)	3695
Lamp category	LED	Mountings	Track
Power (W)	35W	Environment	Indoor
CCT (K)	4000K		
CRI	80		



### Optical


Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Flood
Beam angle (°)	45
Beam angle C90-270 (°)	45



Beam Angle: 45°

h(m)	E(lx)	D(m)
1	7522	0.83
2	1880	1.65
3	836	2.48
4	470	3.31
5	301	4.13

Luminous flux luminaire  
3695 lm




### Electrical

Frequency (Hz)	50/60
Dimmable	Yes
Driver	Integrated
Emergency	Without
Insulation class	I

### Physical

Color	Black
Orientation	Adjustable
Weight (kg)	1.70
Rotation (°)	360



## Solid Pure Track Dali Version




---

Holding ring  
08.8768.14




---

Honeycomb anti-glare screen  
08.8763.14




---

Blue filter  
08.8766.64.OD




---

Sky blue filter  
08.8766.65.OD



---

Amber filter  
08.8766.66.OD



---

Red filter  
08.8766.67.OD