

Solid Pure Track Dali Version

09.2961.30.DA - White


Spotlight to be installed on 3-phase track with LED light source. 220-240V, 50-60Hz power supply included.

Main specifications

Number of heads	1	Net lumen (lm)	3695
Lamp category	LED	Mountings	Track
Power (W)	35W	Environment	Indoor
CCT (K)	4000K		
CRI	80		

Optical

Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Flood
Beam angle (°)	45
Beam angle C90-270 (°)	45



Beam Angle:	45°		
	h(m)	E(lx)	D(m)
1	7522	0.83	
2	1880	1.65	
3	836	2.48	
4	470	3.31	
5	301	4.13	

Luminous flux luminaire
3695 lm


Electrical

Frequency (Hz)	50/60
Dimmable	Yes
Driver	Integrated
Emergency	Without
Insulation class	I

Physical

Color	White
Orientation	Adjustable
Weight (kg)	1.70
Rotation (°)	360


Certification / Marking




Solid Pure Track Dali Version




Honeycomb anti-glare screen
08.8763.14




Blue filter
08.8766.64.OD



Sky blue filter
08.8766.65.OD



Amber filter
08.8766.66.OD



Red filter
08.8766.67.OD



Holding ring
08.8768.14