

Solid Pure Track Dali Version

09.2961.30.DA - White

Spotlight to be installed on 3-phase track with LED light source. 220-240V, 50-60Hz power supply included.

Main specifications

Number of heads	1	**Net lumen (lm)**	3695
Lamp category	LED	**Mountings**	Track
Power (W)	35W	**Environment**	Indoor dry location
CCT (K)	4000K		
CRI	80		

Optical

Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Flood
Beam angle (°)	45
Beam angle C90-270 (°)	45



Luminous flux luminaire
3695 lm

Beam Angle: 45°

h(m)	E(lx)	D(m)
1	7522	0.83
2	1880	1.65
3	836	2.48
4	470	3.31
5	301	4.13

Electrical

Frequency (Hz)	50/60	**Insulation class**	I
Dimmable	Yes		
Driver	Integrated		
Driver type	Dimmable DALI		
	1		
Emergency	Without		

Physical

Color	White
Orientation	Adjustable
Weight (kg)	1.70
Rotation (°)	360

Solid Pure Track Dali Version

Honeycomb anti-glare screen
08.8763.14



Red filter
08.8766.67.OD



Amber filter
08.8766.66.OD



Sky blue filter
08.8766.65.OD



Blue filter
08.8766.64.OD

Holding ring
08.8768.14