

## Solid Pure Track Dali Version

09.2967.30.DA - White


Spotlight to be installed on 3-phase track with LED light source. 220-240V, 50-60Hz power supply included.

### Main specifications

<b>Number of heads</b>	1	<b>Net lumen (lm)</b>	4609
<b>Lamp category</b>	LED	<b>Mountings</b>	Track
<b>Power (W)</b>	53W	<b>Environment</b>	Indoor dry location
<b>CCT (K)</b>	3000K		
<b>CRI</b>	80		

### Optical

<b>Lighting type</b>	Direct
<b>LED type</b>	LED array
<b>Light distribution</b>	Symmetric
<b>Optical type</b>	Flood
<b>Beam angle (°)</b>	45
<b>Beam angle C90-270 (°)</b>	45



<b>Beam Angle:</b>	45°		
<b>h(m)</b>	<b>E(lx)</b>	<b>D(m)</b>	
1	9417	0.82	
2	2354	1.65	
3	1046	2.47	
4	589	3.30	
5	377	4.12	

Luminous flux luminaire  
4609 lm

### Electrical

<b>Frequency (Hz)</b>	50/60	<b>Insulation class</b>	I
<b>Dimmable</b>	Yes		
<b>Driver</b>	Integrated		
<b>Driver type</b>	Dimmable DALI		
	1		
<b>Emergency</b>	Without		

### Physical


<b>Color</b>	White
<b>Orientation</b>	Adjustable
<b>Weight (kg)</b>	1.70
<b>Rotation (°)</b>	360

## Solid Pure Track Dali Version




---

Holding ring  
08.8768.14




---

Sky blue filter  
08.8766.65.OD




---

Blue filter  
08.8766.64.OD



---

Red filter  
08.8766.67.OD



---

Amber filter  
08.8766.66.OD



---

Honeycomb anti-glare screen  
08.8763.14