

Solid Pure Track Dali Version

■ 09.2973.14.DA - Black


Spotlight to be installed on 3-phase track with LED light source. 220-240V, 50-60Hz power supply included.

Main specifications

| | | | |
|-----------------|-------|----------------|--------|
| Number of heads | 1 | Net lumen (lm) | 4892 |
| Lamp category | LED | Mountings | Track |
| Power (W) | 53W | Environment | Indoor |
| CCT (K) | 4000K | | |
| CRI | 80 | | |

Optical

| | |
|------------------------|-----------|
| Lighting type | Direct |
| LED type | LED array |
| Light distribution | Symmetric |
| Optical type | Flood |
| Beam angle (°) | 45 |
| Beam angle C90-270 (°) | 45 |



| | | | |
|-------------|------|-------|------|
| Beam Angle: | 45° | | |
| | h(m) | E(lx) | D(m) |
| 1 | 9995 | 0.82 | |
| 2 | 2499 | 1.65 | |
| 3 | 1111 | 2.47 | |
| 4 | 625 | 3.30 | |
| 5 | 400 | 4.12 | |

Luminous flux luminaire
4892 lm


Electrical

| | |
|------------------|------------|
| Frequency (Hz) | 50/60 |
| Dimmable | Yes |
| Driver | Integrated |
| Emergency | Without |
| Insulation class | I |

Physical

| | |
|--------------|------------|
| Color | Black |
| Orientation | Adjustable |
| Weight (kg) | 1.70 |
| Rotation (°) | 360 |


Certification / Marking




Solid Pure Track Dali Version




Honeycomb anti-glare screen
08.8763.14




Blue filter
08.8766.64.OD



Sky blue filter
08.8766.65.OD



Amber filter
08.8766.66.OD



Red filter
08.8766.67.OD



Holding ring
08.8768.14