

## Solid Pure Track Dali Version

■ 09.2978.14.DA - Black


Spotlight to be installed on 3-phase track with LED light source. 220-240V, 50-60Hz power supply included.

### Main specifications

|                 |       |                |                     |
|-----------------|-------|----------------|---------------------|
| Number of heads | 1     | Net lumen (lm) | 3806                |
| Lamp category   | LED   | Mountings      | Track               |
| Power (W)       | 53W   | Environment    | Indoor dry location |
| CCT (K)         | 3000K |                |                     |
| CRI             | 90    |                |                     |

### Optical

|                        |           |
|------------------------|-----------|
| Lighting type          | Direct    |
| LED type               | LED array |
| Light distribution     | Symmetric |
| Optical type           | Medium    |
| Beam angle (°)         | 23        |
| Beam angle C90-270 (°) | 23        |



Beam Angle: 23°

|   | h(m)  | E(lx) | D(m) |
|---|-------|-------|------|
| 1 | 16226 | 0.40  |      |
| 2 | 4056  | 0.80  |      |
| 3 | 1803  | 1.20  |      |
| 4 | 1014  | 1.59  |      |
| 5 | 649   | 1.99  |      |

Luminous flux luminaire  
3806 lm



### Electrical

|                |               |                  |   |
|----------------|---------------|------------------|---|
| Frequency (Hz) | 50/60         | Insulation class | I |
| Dimmable       | Yes           |                  |   |
| Driver         | Integrated    |                  |   |
| Driver type    | Dimmable DALI |                  |   |
|                | 1             |                  |   |
| Emergency      | Without       |                  |   |

### Physical

|              |            |
|--------------|------------|
| Color        | Black      |
| Orientation  | Adjustable |
| Weight (kg)  | 1.70       |
| Rotation (°) | 360        |

Solid Pure Track Dali Version



---



Blue filter  
08.8766.64.OD

---

Honeycomb anti-glare screen  
08.8763.14

---

Red filter  
08.8766.67.OD



---

Holding ring  
08.8768.14

---

Amber filter  
08.8766.66.OD

---

Sky blue filter  
08.8766.65.OD