

## Solid Pure Track Dali Version

09.2992.30.DA - White


Spotlight to be installed on 3-phase track with LED light source. 220-240V, 50-60Hz power supply included.

### Main specifications

Number of heads	1	Net lumen (lm)	2814
Lamp category	LED	Mountings	Track
Power (W)	35W	Environment	Indoor
CCT (K)	3000K		
CRI	90		

### Optical

Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Medium
Beam angle (°)	23
Beam angle C90-270 (°)	23



Beam Angle: 23°

	h(m)	E(lx)	D(m)
1	11990	0.40	
2	2997	0.80	
3	1332	1.20	
4	749	1.59	
5	480	1.99	

Luminous flux luminaire  
2814 lm


### Electrical

Frequency (Hz)	50/60
Dimmable	Yes
Driver	Integrated
Emergency	Without
Insulation class	I

### Physical

Color	White
Orientation	Adjustable
Weight (kg)	1.70
Rotation (°)	360

### Certification / Marking




## Solid Pure Track Dali Version




---

Honeycomb anti-glare screen  
08.8763.14




---

Blue filter  
08.8766.64.OD




---

Sky blue filter  
08.8766.65.OD



---

Amber filter  
08.8766.66.OD



---

Red filter  
08.8766.67.OD



---

Holding ring  
08.8768.14