



Solid Pure Track No Dimmable

■ 09.2871.30 - White


Spotlight to be installed on 3-phase track with LED light source. 220-240V, 50-60Hz power supply included.

Main specifications

Number of heads	1	Net lumen (lm)	2799
Lamp category	LED	Mountings	Track
Power (W)	30W	Environment	Indoor dry location
CCT (K)	3000K		
CRI	80		

Optical


Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Medium
Beam angle (°)	22
Beam angle C90-270 (°)	22



Beam Angle: 22°

	h(m)	E(lx)	D(m)
1	12167	0.39	
2	3042	0.79	
3	1352	1.18	
4	760	1.57	
5	487	1.97	

Luminous flux luminaire
2799 lm




Electrical



Frequency (Hz)	50/60	Insulation class	I
Dimmable	No		
Driver	Integrated		
Driver type	Non Dimmable		
Emergency	Without		

Physical

Color	White
Orientation	Adjustable
Weight (kg)	1.70
Rotation (°)	360



Solid Pure Track No Dimmable



Blue filter
08.8766.64.OD

Holding ring
08.8768.14



Amber filter
08.8766.66.OD



Honeycomb anti-glare screen
08.8763.14

Recessed box for fix-point
60.3022.11

Fix-point
60.3023.29



Red filter
08.8766.67.OD

Recessed box for fix-point
60.3022.14

Sky blue filter
08.8766.65.OD



Fix-point
60.3023.11



Fix-point
60.3023.14