

## Solid Pure Track No Dimmable

■ 09.2885.14 - Black


Spotlight to be installed on 3-phase track with LED light source. 220-240V, 50-60Hz power supply included.

### Main specifications

<b>Number of heads</b>	1	<b>Net lumen (lm)</b>	1832
<b>Lamp category</b>	LED	<b>Mountings</b>	Track
<b>Power (W)</b>	23W	<b>Environment</b>	Indoor dry location
<b>CCT (K)</b>	3000K		
<b>CRI</b>	90		

### Optical

<b>Lighting type</b>	Direct
<b>LED type</b>	LED array
<b>Light distribution</b>	Symmetric
<b>Optical type</b>	Spot
<b>Beam angle (°)</b>	10
<b>Beam angle C90-270 (°)</b>	10



Beam Angle: 10°

	h(m)	E(lx)	D(m)
1	22949	0.18	
2	5737	0.35	
3	2550	0.53	
4	1434	0.71	
5	918	0.88	

Luminous flux luminaire  
1832 lm


### Electrical

<b>Frequency (Hz)</b>	50/60	<b>Insulation class</b>	I
<b>Dimmable</b>	No		
<b>Driver</b>	Integrated		
<b>Driver type</b>	Non Dimmable		
<b>Emergency</b>	Without		

### Physical

<b>Color</b>	Black
<b>Orientation</b>	Adjustable
<b>Weight (kg)</b>	1.70
<b>Rotation (°)</b>	360

# Solid Pure Track No Dimmable




---

Sky blue filter  
08.8766.65.OD



---

Fix-point  
60.3023.11




---

Blue filter  
08.8766.64.OD



---

Honeycomb anti-glare screen  
08.8763.14



---

Amber filter  
08.8766.66.OD



---

Recessed box for fix-point  
60.3022.14



---

Holding ring  
08.8768.14




---

Recessed box for fix-point  
60.3022.11



---

Fix-point  
60.3023.29



---

Fix-point  
60.3023.14

Red filter  
08.8766.67.OD