



## Solid Pure Track No Dimmable

09.2899.30 - White


Spotlight to be installed on 3-phase track with LED light source. 220-240V, 50-60Hz power supply included.

### Main specifications

<b>Number of heads</b>	1	<b>Net lumen (lm)</b>	2213
<b>Lamp category</b>	LED	<b>Mountings</b>	Track
<b>Power (W)</b>	23W	<b>Environment</b>	Indoor dry location
<b>CCT (K)</b>	4000K		
<b>CRI</b>	80		

### Optical


<b>Lighting type</b>	Direct
<b>LED type</b>	LED array
<b>Light distribution</b>	Symmetric
<b>Optical type</b>	Flood
<b>Beam angle (°)</b>	35
<b>Beam angle C90-270 (°)</b>	35



Beam Angle: 35°

	h(m)	E(lx)	D(m)
1	5662	0.64	
2	1415	1.27	
3	629	1.91	
4	354	2.54	
5	226	3.18	

Luminous flux luminaire  
2213 lm




### Electrical

<b>Frequency (Hz)</b>	50/60	<b>Insulation class</b>	I
<b>Dimmable</b>	No		
<b>Driver</b>	Integrated		
<b>Driver type</b>	Non Dimmable		
<b>Emergency</b>	Without		

### Physical

<b>Color</b>	White
<b>Orientation</b>	Adjustable
<b>Weight (kg)</b>	1.70
<b>Rotation (°)</b>	360



## Solid Pure Track No Dimmable




---

Holding ring  
08.8768.14



---

Fix-point  
60.3023.14



---

Red filter  
08.8766.67.OD




---

Fix-point  
60.3023.11



---

Honeycomb anti-glare screen  
08.8763.14




---

Amber filter  
08.8766.66.OD




---

Recessed box for fix-point  
60.3022.14



---

Sky blue filter  
08.8766.65.OD



---

Blue filter  
08.8766.64.OD



---

Recessed box for fix-point  
60.3022.11

---

Fix-point  
60.3023.29