

Solid Pure Track No Dimmable

■ 09.2953.30 - White


Spotlight to be installed on 3-phase track with LED light source. 220-240V, 50-60Hz power supply included.

Main specifications

Number of heads	1	Net lumen (lm)	3474
Lamp category	LED	Mountings	Track
Power (W)	35W	Environment	Indoor dry location
CCT (K)	3000K		
CRI	80		

Optical

Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Spot
Beam angle (°)	15
Beam angle C90-270 (°)	15



Beam Angle: 15°

	h(m)	E(lx)	D(m)
1	23575	0.26	
2	5894	0.53	
3	2619	0.79	
4	1473	1.05	
5	943	1.31	

Luminous flux luminaire
3474 lm

Electrical

Frequency (Hz)	50/60	Insulation class	I
Dimmable	No		
Driver	Integrated		
Driver type	Non Dimmable		
Emergency	Without		


Physical

Color	White
Orientation	Adjustable
Weight (kg)	1.70
Rotation (°)	360

Solid Pure Track No Dimmable




Fix-point
60.3023.14



Sky blue filter
08.8766.65.OD



Honeycomb anti-glare screen
08.8763.14



Blue filter
08.8766.64.OD




Holding ring
08.8768.14



Recessed box for fix-point
60.3022.11



Fix-point
60.3023.29



Red filter
08.8766.67.OD



Amber filter
08.8766.66.OD



Recessed box for fix-point
60.3022.14



Fix-point
60.3023.11