


# Solid Pure Track No Dimmable

## 09.2967.14 - Black

Spotlight to be installed on 3-phase track with LED light source. 220-240V, 50-60Hz power supply included.

## Main specifications

| | | | |
|---|---|---|---|
| **Number of heads** | 1 | **Net lumen (lm)** | 4609 |
| **Lamp category** | LED | **Mountings** | Track |
| **Power (W)** | 53W | **Environment** | Indoor dry location |
| **CCT (K)** | 3000K | | |
| **CRI** | 80 | | |

## Optical

| | |
|---|---|
| **Lighting type** | Direct |
| **LED type** | LED array |
| **Light distribution** | Symmetric |
| **Optical type** | Flood |
| **Beam angle (°)** | 45 |
| **Beam angle C90-270 (°)** | 45 |




Luminous flux luminaire
4609 lm

Beam Angle: 45°

| h(m) | E(lx) | D(m) |
|---|---|---|
| 1 | 9417 | 0.82 |
| 2 | 2354 | 1.65 |
| 3 | 1046 | 2.47 |
| 4 | 589 | 3.30 |
| 5 | 377 | 4.12 |

## Electrical

| | | | |
|---|---|---|---|
| **Frequency (Hz)** | 50/60 | **Insulation class** | I |
| **Dimmable** | No | | |
| **Driver** | Integrated | | |
| **Driver type** | Non Dimmable | | |
| **Emergency** | Without | | |

## Physical

| | |
|---|---|
| **Color** | Black |
| **Orientation** | Adjustable |
| **Weight (kg)** | 1.70 |
| **Rotation (°)** | 360 |

# Solid Pure Track No Dimmable

Holding ring
08.8768.14

Fix-point
60.3023.11



Blue filter
08.8766.64.OD

Honeycomb anti-glare screen
08.8763.14

Recessed box for fix-point
60.3022.11

Fix-point
60.3023.29



Amber filter
08.8766.66.OD



Sky blue filter
08.8766.65.OD

Fix-point
60.3023.14



Red filter
08.8766.67.OD

Recessed box for fix-point
60.3022.14