

Solid Pure Track No Dimmable

09.2972.30 - White


Spotlight to be installed on 3-phase track with LED light source. 220-240V, 50-60Hz power supply included.

Main specifications

Number of heads	1	Net lumen (lm)	4948
Lamp category	LED	Mountings	Track
Power (W)	53W	Environment	Indoor dry location
CCT (K)	4000K		
CRI	80		

Optical

Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Medium
Beam angle (°)	23
Beam angle C90-270 (°)	23



Beam Angle: 23°

	h(m)	E(lx)	D(m)
1	21094	0.40	
2	5274	0.80	
3	2344	1.20	
4	1318	1.59	
5	844	1.99	

Luminous flux luminaire
4948 lm


Electrical

Frequency (Hz)	50/60	Insulation class	I
Dimmable	No		
Driver	Integrated		
Driver type	Non Dimmable		
Emergency	Without		

Physical

Color	White
Orientation	Adjustable
Weight (kg)	1.70
Rotation (°)	360


Solid Pure Track No Dimmable



Red filter
08.8766.67.OD

Fix-point
60.3023.14



Fix-point
60.3023.11



Honeycomb anti-glare screen
08.8763.14

Fix-point
60.3023.29

Amber filter
08.8766.66.OD



Sky blue filter
08.8766.65.OD

Recessed box for fix-point
60.3022.11

Blue filter
08.8766.64.OD



Holding ring
08.8768.14



Recessed box for fix-point
60.3022.14