

1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	IP 20	RETILAP GWT 850°
SPOT =		

Solid Pure Track No Dimmable

09.2977.14 - Black

Spotlight to be installed on 3-phase track with LED light source. 220-240V, 50-60Hz power supply included.

Main specifications

 Number of heads
 1

 Lamp category
 LED

 Power (W)
 53W

 CCT (K)
 3000K


 CRI
 90

Net lumen (lm) 3848 Mountings Track

Environment Indoor dry location

Optical

Lighting typeDirectLED typeLED arrayLight distributionSymmetricOptical typeSpotBeam angle (°)15Beam angle C90-270 (°)15



Luminous flux luminaire 3848 lm

Ве	15°	
h(n	n) E(l x)	D(m
1	26199	0.26
2	6550	0.52
3	2911	0.78
4	1637	1.05
5	1048	1 31

Electrical

Frequency (Hz) 50/60
Dimmable No
Driver Integrated
Driver type Non Dimmable
Emergency Without

Insulation class

Physical

ColorBlackOrientationAdjustableWeight (kg)1.70Rotation (°)360

Solid Pure Track No Dimmable







Fix-point 60.3023.14

Red filter 08.8766.67.OD

Fix-point 60.3023.11







Holding ring 08.8768.14

Sky blue filter 08.8766.65.OD

Blue filter 08.8766.64.OD








Honeycomb anti-glare screen 08.8763.14

Recessed box for fix-point 60.3022.11

Fix-point 60.3023.29





Amber filter 08.8766.66.OD Recessed box for fix-point 60.3022.14