

## Solid Pure Track No Dimmable

09.2979.30 - White


Spotlight to be installed on 3-phase track with LED light source. 220-240V, 50-60Hz power supply included.

### Main specifications

|                 |       |                |                     |
|-----------------|-------|----------------|---------------------|
| Number of heads | 1     | Net lumen (lm) | 3763                |
| Lamp category   | LED   | Mountings      | Track               |
| Power (W)       | 53W   | Environment    | Indoor dry location |
| CCT (K)         | 3000K |                |                     |
| CRI             | 90    |                |                     |

### Optical

|                        |           |
|------------------------|-----------|
| Lighting type          | Direct    |
| LED type               | LED array |
| Light distribution     | Symmetric |
| Optical type           | Flood     |
| Beam angle (°)         | 45        |
| Beam angle C90-270 (°) | 45        |



Beam Angle: 45°

| h(m) | E(lx) | D(m) |
|------|-------|------|
| 1    | 7688  | 0.82 |
| 2    | 1922  | 1.65 |
| 3    | 854   | 2.47 |
| 4    | 481   | 3.30 |
| 5    | 308   | 4.12 |

Luminous flux luminaire  
3763 lm

### Electrical

|                |              |                  |   |
|----------------|--------------|------------------|---|
| Frequency (Hz) | 50/60        | Insulation class | I |
| Dimmable       | No           |                  |   |
| Driver         | Integrated   |                  |   |
| Driver type    | Non Dimmable |                  |   |
| Emergency      | Without      |                  |   |

### Physical

|              |            |
|--------------|------------|
| Color        | White      |
| Orientation  | Adjustable |
| Weight (kg)  | 1.70       |
| Rotation (°) | 360        |

Solid Pure Track No Dimmable



Recessed box for fix-point  
60.3022.11



Amber filter  
08.8766.66.OD



Recessed box for fix-point  
60.3022.14



Fix-point  
60.3023.11




Fix-point  
60.3023.11



Holding ring  
08.8768.14




Fix-point  
60.3023.29



Blue filter  
08.8766.64.OD




Honeycomb anti-glare screen  
08.8763.14



---

Sky blue filter  
08.8766.65.OD



---

Red filter  
08.8766.67.OD