

Solid Pure Track No Dimmable

■ 09.2993.14 - Black


Spotlight to be installed on 3-phase track with LED light source. 220-240V, 50-60Hz power supply included.

Main specifications

Number of heads	1	Net lumen (lm)	2783
Lamp category	LED	Mountings	Track
Power (W)	35W	Environment	Indoor dry location
CCT (K)	3000K		
CRI	90		

Optical

Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Flood
Beam angle (°)	45
Beam angle C90-270 (°)	45



Beam Angle: 45°

h(m)	E(lx)	D(m)
1	5665	0.83
2	1416	1.65
3	629	2.48
4	354	3.31
5	227	4.13

Luminous flux luminaire
2783 lm

Electrical

Frequency (Hz)	50/60	Insulation class	I
Dimmable	No		
Driver	Integrated		
Driver type	Non Dimmable		
Emergency	Without		


Physical

Color	Black
Orientation	Adjustable
Weight (kg)	1.70
Rotation (°)	360

Solid Pure Track No Dimmable



Fix-point
60.3023.14



Red filter
08.8766.67.OD



Holding ring
08.8768.14




Recessed box for fix-point
60.3022.11




Fix-point
60.3023.29




Recessed box for fix-point
60.3022.14



Amber filter
08.8766.66.OD



Sky blue filter
08.8766.65.OD



Blue filter
08.8766.64.OD



Fix-point
60.3023.11



Honeycomb anti-glare screen
08.8763.14