

## Solid Pure Track No Dimmable

09.2998.30 - White


Spotlight to be installed on 3-phase track with LED light source. 220-240V, 50-60Hz power supply included.

### Main specifications

|                 |       |                |                     |
|-----------------|-------|----------------|---------------------|
| Number of heads | 1     | Net lumen (lm) | 2486                |
| Lamp category   | LED   | Mountings      | Track               |
| Power (W)       | 30W   | Environment    | Indoor dry location |
| CCT (K)         | 3000K |                |                     |
| CRI             | 90    |                |                     |

### Optical

|                        |           |
|------------------------|-----------|
| Lighting type          | Direct    |
| LED type               | LED array |
| Light distribution     | Symmetric |
| Optical type           | Medium    |
| Beam angle (°)         | 22        |
| Beam angle C90-270 (°) | 22        |



Beam Angle: 22°

| h(m) | E(lx) | D(m) |
|------|-------|------|
| 1    | 10807 | 0.39 |
| 2    | 2702  | 0.79 |
| 3    | 1201  | 1.18 |
| 4    | 675   | 1.57 |
| 5    | 432   | 1.97 |

Luminous flux luminaire  
2486 lm

### Electrical

|                |              |                  |   |
|----------------|--------------|------------------|---|
| Frequency (Hz) | 50/60        | Insulation class | I |
| Dimmable       | No           |                  |   |
| Driver         | Integrated   |                  |   |
| Driver type    | Non Dimmable |                  |   |
| Emergency      | Without      |                  |   |

### Physical

|              |            |
|--------------|------------|
| Color        | White      |
| Orientation  | Adjustable |
| Weight (kg)  | 1.70       |
| Rotation (°) | 360        |

Solid Pure Track No Dimmable



Amber filter  
08.8766.66.OD




Recessed box for fix-point  
60.3022.11



Fix-point  
60.3023.29




Honeycomb anti-glare screen  
08.8763.14




Red filter  
08.8766.67.OD



Recessed box for fix-point  
60.3022.14



Sky blue filter  
08.8766.65.OD



Blue filter  
08.8766.64.OD



Holding ring  
08.8768.14



---

Fix-point  
60.3023.11



---

Fix-point  
60.3023.14