



Spot

New

■ 03.2238.14A - Black


Accent lighting LED module to be installed in The Running Magnet System. Built-in DC/DC electronic voltage converter.

Main specifications

Number of heads	1	CRI	90
Lamp category	LED	Net lumen (lm)	356
Power (W)	6W	Mountings	Track
System power (W)	6	Environment	Indoor dry location
CCT (K)	5000K		

Optical

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Medium
Beam angle (°)	20
Beam angle C90-270 (°)	20
UGRL	10
Efficiency (lm/W)	59.33



Beam Angle: 20°

h(m) E(lx) D(m)

1 2105 0.35

2 526 0.71

3 234 1.06

4 132 1.41

5 84 1.77



Luminous flux luminaire
356 lm

Electrical

Voltage (V)	24	Insulation class	III
Dimmable	Yes		
Driver	Remote excluded		
Driver type	Electronic 12V, Dimmable		
	Casambi, Dimmable 1-10V, Dimmable DALI 1		
Emergency	Without		

Physical

Color	Black	Spot diameter (mm)	35
Orientation	Adjustable	Length (mm)	41
Weight (kg)	0.07		
Tilt (°)	90		
Rotation (°)	267		



Spot



Honeycomb
08.0191.14