



Spot 120 Casambi integrated

New

03.6284.14.CB - Black


Accent lighting LED module to be installed in The Running Magnet System. Built-in DC/DC electronic voltage converter.

Main specifications

| | | | |
|------------------|-------|----------------|---------------------|
| Number of heads | 1 | CRI | 90 |
| Lamp category | LED | Net lumen (lm) | 731 |
| Power (W) | 12.5W | Mountings | Track |
| System power (W) | 13 | Environment | Indoor dry location |
| CCT (K) | 3000K | | |

Optical

| | |
|------------------------|-----------|
| Lighting type | Direct |
| LED type | Power LED |
| Light distribution | Symmetric |
| Optical type | Spot |
| Beam angle (°) | 25 |
| Beam angle C90-270 (°) | 25 |
| UGRL | 5 |
| Efficiency (lm/W) | 56.23 |



Beam Angle: 25°

| h(m) | E(lx) | D(m) |
|------|-------|------|
| 1 | 3441 | 0.45 |
| 2 | 860 | 0.89 |
| 3 | 382 | 1.34 |
| 4 | 215 | 1.78 |
| 5 | 138 | 2.23 |

Luminous flux luminaire
731 lm (EXTREME CUT OFF)

Electrical

| | | | |
|-------------|-----------------|------------------|-----|
| Voltage (V) | 24.00 | Insulation class | III |
| Dimmable | Yes | | |
| Driver | Remote excluded | | |
| Driver type | Dimmable | | |
| Emergency | Casambi | | |
| | Without | | |

Physical

| | | | |
|--------------|------------|--------------------|--------|
| Color | Black | Spot diameter (mm) | 46 |
| Orientation | Adjustable | Length (mm) | 46 |
| Weight (kg) | 0.35 | Lifespan (L70 B10) | L80B50 |
| Tilt (°) | 90 | | |
| Rotation (°) | 360 | | |

Note

Maximum 14 spots for a single driver. Accessories included (honeycomb and screening crosspiece). The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® by Casambi.

