



## Spot 120 Casambi integrated

New

03.6284.40.CB - White


Accent lighting LED module to be installed in The Running Magnet System. Built-in DC/DC electronic voltage converter.

### Main specifications

<b>Number of heads</b>	1	<b>CRI</b>	90
<b>Lamp category</b>	LED	<b>Net lumen (lm)</b>	731
<b>Power (W)</b>	12.5W	<b>Mountings</b>	Track
<b>System power (W)</b>	13	<b>Environment</b>	Indoor dry location
<b>CCT (K)</b>	3000K		

### Optical

<b>Lighting type</b>	Direct
<b>LED type</b>	Power LED
<b>Light distribution</b>	Symmetric
<b>Optical type</b>	Spot
<b>Beam angle (°)</b>	25
<b>Beam angle C90-270 (°)</b>	25
<b>UGRL</b>	5
<b>Efficiency (lm/W)</b>	56.23



Beam Angle: 25°

h(m)	E(lx)	D(m)
1	3441	0.45
2	860	0.89
3	382	1.34
4	215	1.78
5	138	2.23

Luminous flux luminaire  
731 lm (EXTREME CUT OFF)




### Electrical

<b>Voltage (V)</b>	24.00	<b>Insulation class</b>	III
<b>Dimmable</b>	Yes		
<b>Driver</b>	Remote excluded		
<b>Driver type</b>	Dimmable		
<b>Emergency</b>	Casambi		
	Without		

### Physical

<b>Color</b>	White	<b>Spot diameter (mm)</b>	46
<b>Orientation</b>	Adjustable	<b>Length (mm)</b>	46
<b>Weight (kg)</b>	0.35	<b>Lifespan (L70 B10)</b>	L80B50
<b>Tilt (°)</b>	90		
<b>Rotation (°)</b>	360		



### Note

Maximum 14 spots for a single driver. Accessories included (honeycomb and screening crosspiece). The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® by Casambi.

