



Spot 120 Casambi integrated

New

■ 03.6285.14.CB - Black


Accent lighting LED module to be installed in The Running Magnet System. Built-in DC/DC electronic voltage converter.

Main specifications

Number of heads	1	Net lumen (lm)	707
Lamp category	LED	Mountings	Track
Power (W)	12.5W	Environment	Indoor dry location
CCT (K)	2700K		
CRI	90		

Optical

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Spot
Beam angle (°)	25
Beam angle C90-270 (°)	25



Beam Angle:	25°		
	h(m)	E(lx)	D(m)
1	3338	0.44	
2	835	0.89	
3	371	1.33	
4	209	1.78	
5	134	2.22	

Luminous flux luminaire
707 lm (EXTREME CUT OFF)




Electrical

Voltage (V)	24.00	Insulation class	III
Dimmable	Yes		
Driver	Remote excluded		
Driver type	Dimmable		
Emergency	Casambi		
	Without		

Physical

Color	Black	Spot diameter (mm)	46
Orientation	Adjustable	Length (mm)	46
Weight (kg)	0.35		
Tilt (°)	90		
Rotation (°)	360		



Note

Maximum 14 spots for a single driver. Accessories included (honeycomb and screening crosspiece). The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® by Casambi.

