



Spot 120 Casambi integrated

New

03.6286.40.CB - White


Accent lighting LED module to be installed in The Running Magnet System. Built-in DC/DC electronic voltage converter.

Main specifications

Number of heads	1	CRI	90
Lamp category	LED	Net lumen (lm)	430
Power (W)	12.5W	Mountings	Track
System power (W)	13	Environment	Indoor dry location
CCT (K)	2700K		

Optical

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Medium
Beam angle (°)	33
Beam angle C90-270 (°)	33
UGRL	9
Efficiency (lm/W)	33.08



Beam Angle: 33°

h(m)	E(lx)	D(m)
1	1345	0.59
2	336	1.17
3	149	1.76
4	84	2.34
5	54	2.93

Luminous flux luminaire
430 lm (EXTREME CUT OFF)

Electrical

Voltage (V)	24.00	Insulation class	III
Dimmable	Yes		
Driver	Remote excluded		
Driver type	Dimmable		
Emergency	Casambi		
	Without		

Physical

Color	White	Spot diameter (mm)	46
Orientation	Adjustable	Length (mm)	46
Weight (kg)	0.35	Lifespan (L70 B10)	L80B50
Tilt (°)	90		
Rotation (°)	360		

Note

Maximum 14 spots for a single driver. Accessories included (honeycomb and screening crosspiece). The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® by Casambi.

