



Spot 120 Casambi integrated

03.8053.05.CB - Polished Aluminium


Accent lighting LED module.

Main specifications

Number of heads	1	Net lumen (lm)	558
Lamp category	LED	Mountings	Track
Power (W)	12W	Environment	Indoor
CCT (K)	3000K		
CRI	90		

Optical


Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Spot
Beam angle (°)	11
Beam angle C90-270 (°)	11



Beam Angle: 11°

h(m)	E(lx)	D(m)
1	11834	0.19
2	2958	0.37
3	1315	0.56
4	740	0.75
5	473	0.93

Luminous flux luminaire
558 lm




Electrical

Voltage (V)	48.00	Insulation class	III
Dimmable	Yes		
Driver	Remote		
Driver type	Electronic dimmable CASAMBI		
Emergency	Without		

Physical

Color	Polished Aluminium	Length (mm)	185
Orientation	Adjustable		
Weight (kg)	0.29		
Tilt (°)	90		
Rotation (°)	360		

Certification / Marking



Note

Accessories included (honeycomb and screening crosspiece). The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® by Casambi.