



Spot 120 Casambi integrated

New

03.8053.05ACB - Polished Aluminium


Accent lighting LED module.

Main specifications

Number of heads	1	CRI	90
Lamp category	LED	Net lumen (lm)	558
Power (W)	12W	Mountings	Track
System power (W)	12	Environment	Indoor dry location
CCT (K)	3000K		

Optical

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Spot
Beam angle (°)	11
Beam angle C90-270 (°)	11
UGRL	3
Efficiency (lm/W)	46.5



Beam Angle: 11°

h(m) E(lx) D(m)

1 11834 0.19

2 2958 0.37

3 1315 0.56

4 740 0.75

5 473 0.93

Luminous flux luminaire
558 lm (EXTREME CUT OFF)

Electrical

Voltage (V)	48	Emergency	Without
Current (mA)	800	Insulation class	III
Dimmable	Yes		
Driver	Remote excluded		
Driver type	Dimmable Casambi		

Physical

Color	Polished Aluminium	Spot diameter (mm)	46
Orientation	Adjustable	Length (mm)	178
Weight (kg)	0.29	Lifespan (L70 B10)	L80B50
Tilt (°)	90		
Rotation (°)	360		

Note

Accessories not suitable for chrome finishes. The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® by Casambi.

