



## Spot 120 Casambi integrated

03.8053.40.CB - White


Accent lighting LED module.

### Main specifications

Number of heads	1	Net lumen (lm)	558
Lamp category	LED	Mountings	Track
Power (W)	12W	Environment	Indoor
CCT (K)	3000K		
CRI	90		

### Optical


Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Spot
Beam angle (°)	11
Beam angle C90-270 (°)	11



Beam Angle: 11°

	h(m)	E(lx)	D(m)
1	11834	0.19	
2	2958	0.37	
3	1315	0.56	
4	740	0.75	
5	473	0.93	

Luminous flux luminaire  
558 lm



### Electrical

Voltage (V)	48.00	Insulation class	III
Dimmable	Yes		
Driver	Remote		
Driver type	Electronic dimmable CASAMBI		
Emergency	Without		

### Physical

Color	White	Length (mm)	185
Orientation	Adjustable		
Weight (kg)	0.29		
Tilt (°)	90		
Rotation (°)	360		

### Certification / Marking



### Note

Accessories included (honeycomb and screening crosspiece). The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® by Casambi.