Spot 120 Casambi integrated

New

03.8054.40ACB - White

Accent lighting LED module.

Main specifications

Number of heads	1	**CRI**	90
Lamp category	LED	**Net lumen (lm)**	487
Power (W)	12W	**Mountings**	Track
System power (W)	12	**Environment**	Indoor dry location
CCT (K)	2700K		

Optical

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Medium
Beam angle (°)	17
Beam angle C90-270 (°)	17
UGRL	4
Efficiency (lm/W)	40.58



Luminous flux luminaire
487 lm (EXTREME CUT OFF)

Beam Angle: 17°

h(m)	E(lx)	D(m)
1	3865	0.29
2	966	0.59
3	429	0.88
4	242	1.18
5	155	1.47



Electrical

Voltage (V)	48	**Emergency**	Without
Current (mA)	800	**Insulation class**	III
Dimmable	Yes		
Driver	Remote excluded		
Driver type	Dimmable Casambi		

Physical

Color	White	**Spot diameter (mm)**	46
Orientation	Adjustable	**Length (mm)**	178
Weight (kg)	0.29	**Lifespan (L70 B10)**	L80B50
Tilt (°)	90		
Rotation (°)	360		

Note

Accessories not suitable for chrome finishes. The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® by Casambi.

IP 20 RETILAP GWT 850°