



Spot 120 Casambi integrated

New

03.8055.05ACB - Polished Aluminium


Accent lighting LED module.

Main specifications

Number of heads	1	Net lumen (lm)	505
Lamp category	LED	Mountings	Track
Power (W)	12W	Environment	Indoor dry location
CCT (K)	3000K		
CRI	90		

Optical

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Medium
Beam angle (°)	17
Beam angle C90-270 (°)	17



Beam Angle: 17°

h(m)	E(lx)	D(m)
1	4006	0.29
2	1001	0.59
3	445	0.88
4	250	1.18
5	160	1.47

Luminous flux luminaire
505 lm (EXTREME CUT OFF)



Electrical

Voltage (V)	48	Insulation class	III
Dimmable	Yes		
Driver	Remote excluded		
Driver type	Dimmable Casambi		
Emergency	Without		

Physical

Color	Polished Aluminium	Length (mm)	185
Orientation	Adjustable		
Weight (kg)	0.29		
Tilt (°)	90		
Rotation (°)	360		

Note

Accessories included (honeycomb and screening crosspiece). The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® by Casambi.

