



New

## Spot 120 Casambi integrated

03.8055.14.CB - Black


Accent lighting LED module.

### Main specifications

|                 |       |                |        |
|-----------------|-------|----------------|--------|
| Number of heads | 1     | Net lumen (lm) | 505    |
| Lamp category   | LED   | Mountings      | Track  |
| Power (W)       | 12W   | Environment    | Indoor |
| CCT (K)         | 3000K |                |        |
| CRI             | 90    |                |        |

### Optical

|                        |           |
|------------------------|-----------|
| Lighting type          | Direct    |
| LED type               | Power LED |
| Light distribution     | Symmetric |
| Optical type           | Medium    |
| Beam angle (°)         | 17        |
| Beam angle C90-270 (°) | 17        |



Beam Angle: 17°

h(m) E(lx) D(m)

1 4006 0.29


2 1001 0.59

3 445 0.88

4 250 1.18

5 160 1.47

Luminous flux luminaire  
505 lm



### Electrical

|             |                             |                  |     |
|-------------|-----------------------------|------------------|-----|
| Voltage (V) | 48.00                       | Insulation class | III |
| Dimmable    | Yes                         |                  |     |
| Driver      | Remote                      |                  |     |
| Driver type | Electronic dimmable CASAMBI |                  |     |
| Emergency   | Without                     |                  |     |

### Physical

|              |            |             |     |
|--------------|------------|-------------|-----|
| Color        | Black      | Length (mm) | 185 |
| Orientation  | Adjustable |             |     |
| Weight (kg)  | 0.29       |             |     |
| Tilt (°)     | 90         |             |     |
| Rotation (°) | 360        |             |     |

### Note

Accessories included (honeycomb and screening crosspiece). The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® by Casambi.

