



## Spot 120 Casambi integrated

New

03.8154.05.CB - Polished Aluminium


Accent lighting LED module.

### Main specifications

Number of heads	1	CRI	90
Lamp category	LED	Net lumen (lm)	654
Power (W)	12.5W	Mountings	Track
System power (W)	12.5	Environment	Indoor dry location
CCT (K)	2700K		

### Optical

Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Medium
Beam angle (°)	17
Beam angle C90-270 (°)	17
UGRL	6
Efficiency (lm/W)	52.32



Beam Angle: 17°

h(m)	E(lx)	D(m)
1	4547	0.31
2	1137	0.61
3	505	0.92
4	284	1.23
5	182	1.53

Luminous flux luminaire  
654 lm



### Electrical

Voltage (V)	48	Emergency	Without
Current (mA)	350	Insulation class	III
Dimmable	Yes		
Driver	Remote excluded		
Driver type	Dimmable Casambi		

### Physical

Color	Polished Aluminium	Spot diameter (mm)	46
Orientation	Adjustable	Length (mm)	178
Weight (kg)	0.29	Lifespan (L70 B10)	L80B50
Tilt (°)	90		
Rotation (°)	360		

### Note

Accessories included (honeycomb and screening crosspiece). The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® by Casambi.

