



Spot 120 Casambi integrated



03.8156.14.CB - Black

Accent lighting LED module.


Main specifications

Number of heads CRI Lamp category LED Net lumen (lm) 599 Power (W) 12.5W Mountings Track

Environment Indoor dry location System power (W) 12.5 CCT (K) 2700K

Optical

Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Flood
Beam angle (°)	40
Beam angle C90-270 (°)	40
UGRL	17
Efficiency (lm/W)	47.92



Beam Angle: 40° h(m) = E(Ix)D(m) 1367 0.73 2 342 1.45 3 152 2.18 4 2.91 85 55 3.64

Luminous flux luminaire 599 lm

Without

Emergency

Insulation class

Electrical


Voltage (V)	48
Current (mA)	350
Dimmable	Yes
Driver	Remote
	excluded
Driver type	Dimmable

Physical

Color	Black	Spot diameter (mm)	46
Orientation	Adjustable	Length (mm)	178
Weight (kg)	0.29	Lifespan (L70 B10)	L80B50
Tilt (°)	90		
Rotation (°)	360		

Casambi











Note

 $Accessories\ included\ (honeycomb\ and\ screening\ crosspiece).\ The\ control\ system\ with\ the\ Casambi\ version\ of\ light$ $fixtures \ is \ directly \ and \ individually \ regulated \ wirelessly \ using \ the \ application \ FLOS \ Control \&by \ Casambi.$