



Spot 120 Casambi integrated

■ 03.8157.14.CB - Black


Accent lighting LED module.

Main specifications

Number of heads	1	Net lumen (lm)	629
Lamp category	LED	Mountings	Track
Power (W)	12.5W	Environment	Indoor
CCT (K)	3000K		
CRI	90		


Optical

Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Flood
Beam angle (°)	40
Beam angle C90-270 (°)	40



Beam Angle:	40°		
h(m)	E(lx)	D(m)	
1	1437	0.73	
2	359	1.45	
3	160	2.18	
4	90	2.91	
5	57	3.64	

Luminous flux luminaire
629 lm



Electrical

Voltage (V)	48.00	Insulation class	III
Dimmable	Yes		
Driver	Remote		
Driver type	Electronic dimmable CASAMBI		
Emergency	Without		

Physical

Color	Black	Length (mm)	185
Orientation	Adjustable		
Weight (kg)	0.29		
Tilt (°)	90		
Rotation (°)	360		

Note

Accessories included (honeycomb and screening crosspiece). The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® by Casambi.

Certification / Marking

