



## Spot 120 Dali Version

■ 03.6284.14ADA - Black


Accent lighting LED module to be installed in The Running Magnet System. Built-in DC/DC electronic voltage converter.

### Main specifications

|                  |       |                |                     |
|------------------|-------|----------------|---------------------|
| Number of heads  | 1     | CRI            | 90                  |
| Lamp category    | LED   | Net lumen (lm) | 731                 |
| Power (W)        | 14W   | Mountings      | Track               |
| System power (W) | 14.5  | Environment    | Indoor dry location |
| CCT (K)          | 3000K |                |                     |

### Optical

|                        |           |
|------------------------|-----------|
| Lighting type          | Direct    |
| LED type               | Power LED |
| Light distribution     | Symmetric |
| Optical type           | Spot      |
| Beam angle (°)         | 25        |
| Beam angle C90-270 (°) | 25        |
| UGRL                   | 5         |
| Efficiency (lm/W)      | 50.41     |



Beam Angle: 25°

|   | h(m) | E(lx) | D(m) |
|---|------|-------|------|
| 1 | 3403 | 0.45  |      |
| 2 | 850  | 0.90  |      |
| 3 | 378  | 1.35  |      |
| 4 | 213  | 1.80  |      |
| 5 | 136  | 2.25  |      |

Luminous flux luminaire  
731 lm

### Electrical

|             |                 |                  |     |
|-------------|-----------------|------------------|-----|
| Voltage (V) | 24              | Insulation class | III |
| Dimmable    | Yes             |                  |     |
| Driver      | Remote excluded |                  |     |
| Driver type | Dimmable DALI   |                  |     |
| Emergency   | Without         |                  |     |

### Physical

|              |            |                    |        |
|--------------|------------|--------------------|--------|
| Color        | Black      | Spot diameter (mm) | 46     |
| Orientation  | Adjustable | Length (mm)        | 46     |
| Weight (kg)  | 0.35       | Lifespan (L70 B10) | L80B50 |
| Tilt (°)     | 90         |                    |        |
| Rotation (°) | 360        |                    |        |

### Note

Maximum 11 spots for a single driver. Accessories included (honeycomb and screening crosspiece). For wireless lighting control, choose integrated Casambi versions.

