



## Spot 120 Dali Version

03.6284.40.DA - White


Accent lighting LED module to be installed in The Running Magnet System. Built-in DC/DC electronic voltage converter.

### Main specifications

Number of heads	1	Net lumen (lm)	731
Lamp category	LED	Mountings	Track
Power (W)	14W	Environment	Indoor
CCT (K)	3000K		
CRI	90		

### Optical


Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Spot
Beam angle (°)	25
Beam angle C90-270 (°)	25



Beam Angle: 25°

h(m)	E(lx)	D(m)
1	3441	0.45
2	860	0.89
3	382	1.34
4	215	1.78
5	138	2.23

Luminous flux luminaire  
731 lm



### Electrical

Voltage (V)	24.00	Insulation class	III
Dimmable	Yes		
Driver	Remote		
Driver type	Electronic		
Emergency	Without		

### Physical

Color	White	Spot diameter (mm)	46
Orientation	Adjustable	Length (mm)	46
Weight (kg)	0.35		
Tilt (°)	90		
Rotation (°)	360		

### Note

Maximum 11 spots for a single driver. Accessories included (honeycomb and screening crosspiece). For wireless lighting control, choose integrated Casambi versions.

