



Spot 120 Dali Version

■ 03.6285.14ADA - Black


Accent lighting LED module to be installed in The Running Magnet System. Built-in DC/DC electronic voltage converter.

Main specifications

Number of heads	1	CRI	90
Lamp category	LED	Net lumen (lm)	707
Power (W)	14W	Mountings	Track
System power (W)	14.5	Environment	Indoor dry location
CCT (K)	2700K		

Optical


Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Spot
Beam angle (°)	25
Beam angle C90-270 (°)	25
UGRL	5
Efficiency (lm/W)	48.76



Beam Angle: 25°

h(m)	E(lx)	D(m)
1	3194	0.46
2	798	0.91
3	355	1.37
4	200	1.82
5	128	2.28

Luminous flux luminaire
707 lm



Electrical

Voltage (V)	24	Insulation class	III
Dimmable	Yes		
Driver	Remote excluded		
Driver type	Dimmable DALI		
Emergency	Without		

Physical

Color	Black	Spot diameter (mm)	46
Orientation	Adjustable	Length (mm)	46
Weight (kg)	0.35	Lifespan (L70 B10)	L80B50
Tilt (°)	90		
Rotation (°)	360		

Note

Maximum 11 spots for a single driver. Accessories included (honeycomb and screening crosspiece). For wireless lighting control, choose integrated Casambi versions.

