


# Spot 120 Dali Version

**03.8052.14ADA - Black**

Accent lighting LED module.

## Main specifications

| | | | |
|---|---|---|---|
| **Number of heads** | 1 | **CRI** | 90 |
| **Lamp category** | LED | **Net lumen (lm)** | 539 |
| **Power (W)** | 12W | **Mountings** | Track |
| **System power (W)** | 12 | **Environment** | Indoor dry location |
| **CCT (K)** | 2700K | | |

## Optical

| | |
|---|---|
| **Lighting type** | Direct |
| **LED type** | Power LED |
| **Light distribution** | Symmetric |
| **Optical type** | Spot |
| **Beam angle (°)** | 11 |
| **Beam angle C90-270 (°)** | 11 |
| **UGRL** | 3 |
| **Efficiency (lm/W)** | 44.92 |




Luminous flux luminaire
539 lm (EXTREME CUT OFF)

Beam Angle: 11°

| h(m) | E(lx) | D(m) |
|---|---|---|
| 1 | 11417 | 0.19 |
| 2 | 2854 | 0.37 |
| 3 | 1269 | 0.56 |
| 4 | 714 | 0.75 |
| 5 | 457 | 0.93 |

## Electrical

| | | | |
|---|---|---|---|
| **Voltage (V)** | 48 | **Emergency** | Without |
| **Current (mA)** | 800 | **Insulation class** | III |
| **Dimmable** | Yes | | |
| **Driver** | Remote excluded | | |
| **Driver type** | Dimmable DALI 1 | | |

## Physical

| | | | |
|---|---|---|---|
| **Color** | Black | **Spot diameter (mm)** | 46 |
| **Orientation** | Adjustable | **Length (mm)** | 178 |
| **Weight (kg)** | 0.29 | **Lifespan (L70 B10)** | L80B50 |
| **Tilt (°)** | 90 | | |
| **Rotation (°)** | 360 | | |

## Note

Accessories included (honeycomb and screening crosspiece). Only compatible with DALI profile version.