



## Spot 120 Dali Version

03.8053.05ADA - Polished Aluminium


Accent lighting LED module.

### Main specifications

<b>Number of heads</b>	1	<b>Net lumen (lm)</b>	558
<b>Lamp category</b>	LED	<b>Mountings</b>	Track
<b>Power (W)</b>	12W	<b>Environment</b>	Indoor dry location
<b>CCT (K)</b>	3000K		
<b>CRI</b>	90		

### Optical


<b>Lighting type</b>	Direct
<b>LED type</b>	Power LED
<b>Light distribution</b>	Symmetric
<b>Optical type</b>	Spot
<b>Beam angle (°)</b>	11
<b>Beam angle C90-270 (°)</b>	11



Beam Angle: 11°

	h(m)	E(lx)	D(m)
1	11834	0.19	
2	2958	0.37	
3	1315	0.56	
4	740	0.75	
5	473	0.93	

Luminous flux luminaire  
558 lm (EXTREME CUT OFF)



### Electrical

<b>Voltage (V)</b>	48	<b>Insulation class</b>	III
<b>Dimmable</b>	Yes		
<b>Driver</b>	Remote excluded		
<b>Driver type</b>	Dimmable DALI		
<b>Emergency</b>	1		
	Without		

### Physical

<b>Color</b>	Polished Aluminium	<b>Length (mm)</b>	185
<b>Orientation</b>	Adjustable		
<b>Weight (kg)</b>	0.29		
<b>Tilt (°)</b>	90		
<b>Rotation (°)</b>	360		

### Note

Accessories included (honeycomb and screening crosspiece). Only compatible with DALI profile version.

