



## Spot 120 Dali Version

03.8054.05ADA - Polished Aluminium


Accent lighting LED module.

### Main specifications

<b>Number of heads</b>	1	<b>Net lumen (lm)</b>	487
<b>Lamp category</b>	LED	<b>Mountings</b>	Track
<b>Power (W)</b>	12W	<b>Environment</b>	Indoor dry location
<b>CCT (K)</b>	2700K		
<b>CRI</b>	90		


### Optical

<b>Lighting type</b>	Direct
<b>LED type</b>	Power LED
<b>Light distribution</b>	Symmetric
<b>Optical type</b>	Medium
<b>Beam angle (°)</b>	17
<b>Beam angle C90-270 (°)</b>	17



Beam Angle: 17°		
h(m)	E(lx)	D(m)
1	3865	0.29
2	966	0.59
3	429	0.88
4	242	1.18
5	155	1.47

Luminous flux luminaire  
487 lm (EXTREME CUT OFF)



### Electrical

<b>Voltage (V)</b>	48	<b>Insulation class</b>	III
<b>Dimmable</b>	Yes		
<b>Driver</b>	Remote excluded		
<b>Driver type</b>	Dimmable DALI		
<b>Emergency</b>	Without		

### Physical

<b>Color</b>	Polished Aluminium	<b>Length (mm)</b>	185
<b>Orientation</b>	Adjustable		
<b>Weight (kg)</b>	0.29		
<b>Tilt (°)</b>	90		
<b>Rotation (°)</b>	360		

### Note

Accessories included (honeycomb and screening crosspiece). Only compatible with DALI profile version.

