



## Spot 120 Dali Version

■ 03.8155.14.DA - Black


Accent lighting LED module.

### Main specifications

|                  |       |                |                     |
|------------------|-------|----------------|---------------------|
| Number of heads  | 1     | CRI            | 90                  |
| Lamp category    | LED   | Net lumen (lm) | 687                 |
| Power (W)        | 12.5W | Mountings      | Track               |
| System power (W) | 12.5  | Environment    | Indoor dry location |
| CCT (K)          | 3000K |                |                     |

### Optical

|                        |           |
|------------------------|-----------|
| Lighting type          | Direct    |
| LED type               | LED array |
| Light distribution     | Symmetric |
| Optical type           | Medium    |
| Beam angle (°)         | 17        |
| Beam angle C90-270 (°) | 17        |
| UGRL                   | 6         |
| Efficiency (lm/W)      | 54.96     |



Beam Angle: 17°

| h(m) | E(lx) | D(m) |
|------|-------|------|
| 1    | 4780  | 0.31 |
| 2    | 1195  | 0.61 |
| 3    | 531   | 0.92 |
| 4    | 299   | 1.23 |
| 5    | 191   | 1.53 |

Luminous flux luminaire  
687 lm

### Electrical

|              |                    |                  |         |
|--------------|--------------------|------------------|---------|
| Voltage (V)  | 48                 | Emergency        | Without |
| Current (mA) | 350                | Insulation class | III     |
| Dimmable     | Yes                |                  |         |
| Driver       | Remote<br>excluded |                  |         |
| Driver type  | Dimmable DALI<br>1 |                  |         |

### Physical

|              |            |                    |        |
|--------------|------------|--------------------|--------|
| Color        | Black      | Spot diameter (mm) | 46     |
| Orientation  | Adjustable | Length (mm)        | 178    |
| Weight (kg)  | 0.29       | Lifespan (L70 B10) | L80B50 |
| Tilt (°)     | 90         |                    |        |
| Rotation (°) | 360        |                    |        |

### Note

Accessories included (honeycomb and screening crosspiece). Only compatible with DALI profile version.

